

PRODUCT DATA SHEET

STOPAQ® GEOTEXTILE

Product Information

Product description: Stopaq® Geotextile is a strong woven geotextile fabric made of polyolefin. It is used as additional mechanical protection for underground coated objects for protection against mechanical impacts and indentations, and prevents ingrowth of roots. Due to its high water permeability it will not influence cathodic protection of buried steel objects.

Features:

- High water permeability
- Additional mechanical protection of coated objects
- UV-resistant
- Rot-free

Benefits:

- · Harmless to environment and workers
- Fast and easy to apply
- Cathodic protection is not negatively influenced

Application examples

Coated pipes and fittings: Additional mechanical protection of underground coated pipes and fittings.

Product properties of Stopaq [®] Geotextile		
Colour	Black, with length-wise and transversal white	
	markings every 25 cm	
Weight	100 g/m²	
Melting point	165°C	
Water permeability	10 l/m².s (ISO 11058)	

General order information			
Product		Stopaq [®] Geotextile is available in rolls or in precut lengths:	
	Art. Nr.:	Product dimensions and contents:	
	1070	 Roll 1m x 100m each (W x L) ~ or ~ 	
		 Per m², to be specified by client. 	
Handling		Handle with care.	
Storage		Store indoor, clean and dry.	
		Unlimited shelf life.	

Information	
Documentation	Extensive information is available on our website. Application instructions and other documentation can be obtained by contacting our head office, from our local distributor or by sending email to info@stopaq.com
Certified staff	Application of the described product should be carried out by certified personnel.



Seal For Life Industries LLC Franklin, MA, USA Tel: +1 508 918 1600 Toll Free: +1 800 248 7659 Fax:+1 508 918 1905 franklin@sealforlife.com Seal For Life Industries Mexico S de R.L. de C.V. Tijuana, Mexico Tel USA: +1 858 633 9740 Fax USA: +1 858 633 9740 Tel Mx: +52 664 647 4397 Fax Mx: +52 664 607 9105 mexico@sealforlife.com Seal For Life Industries Stopaq B.V. Stadskanaal, the Netherlands Tel: +31 599 696 170 Fax: +31 599 696 177 info@sealforlife.com Seal For Life Industries BVBA Westerlo, Belgium Tel: +32 14 722 500 Fax: +32 14 722 570 belgium@sealforlife.com Seal For Life India Private Ltd. Baroda, India Tel: +91 2667 264 721 Fax: +91 2667 264 724

Anodeflex® - Stopaq® - Polyken® - Covalence® - Powercrete® - Sealtaq® - Blockr® - Easy.Qote® - SynergyQ® - Protecta-mesh®

DISCLAIMER: Seal For Life Industries warrants that the product(s) represented within conform(s) to its/their chemical and physical description and is appropriate for the use as stated on the respective technical data sheet when used in compliance with Seal For Life Industries written instructions. Since many installation factors are beyond the control of Seal For Life Industries, the user is obligated to determine the suitability of the products for the intended use and assume all risks and liabilities in connection herewith. Seal For Life Industries liability is stated in the standard terms and conditions of sale. Seal For Life Industries makes no other warranty either expressed or implied. All information contained in the respective technical data sheet(s) should be used as a guide and is subject to change without notice. This document supersedes all previous revisions. Please see revision date on the left. Stopaq® is a registered trademark of Seal For Life Industries.

V 2 / 20161207 (EN) Page 1 /